



- NOTES:
1. ALL DIMENSIONS ARE IN INCHES.
 2. ALL UNDIMENSIONED PICTORIAL CONFIGURATIONS ARE FOR REFERENCE ONLY.
 3. FRONT AND REAR MARKING FOR REFERENCE ONLY.
 4. FINISH: CLEAR IRRIDITE THEN PRIME & PAINT.

LEDS COLOR DESIGNATION

LED	COLOR
UPS ON BATT	RED
UPS FAULT	RED
LOW BATT	RED
INPUT FAULT	RED
UPS OVERLD	RED
OVER TEMP	RED
UPS ON	GREEN
CHARGED	BI-COLOR

* SHORT PIN 1 TO 2 TO TURN UPS ON
 ** 0-5V SIGNAL INDICATE 0-100% LOAD PROPORTIONALLY

CONNECTORS PIN DESIGNATION

J1 AC INPUT
MS3102R16-10P

PIN	DESCRIPTION
A	LINE
B	NEUTRAL
C	GROUND

J2 REMOTE CONTROL
D38999/20WB35SN

PIN	DESCRIPTION
1	REMOTE ON/OFF *
2	
3	LOAD INDICATOR **
4	SIGNAL GND
5-13	SPARE

J3 DC OUTPUT
D38999/20WB98SN

PIN	DESCRIPTION
A	+140 VDC
E	NOT USED
B	- 140 VDC
C	NOT USED
D	NOT USED
F	GND

PAPER COPIES SHALL BE SHREDDED WHEN NO LONGER REQUIRED. ELECTRONIC COPIES SHALL NOT BE DISCLOSED OUTSIDE OF THE INTENDED RECIPIENTS.

THIS DOCUMENT CONTAINS INFORMATION WHICH IS CONFIDENTIAL, MAY BE COMPANY PROPRIETARY, AND MAY BE CONSIDERED CUI. INFORMATION SHOULD BE PROTECTED IN ACCORDANCE WITH ESTABLISHED PROCEDURES & POLICIES.

NOVA ELECTRIC
A DIV. OF TECHNOLOGY DYNAMICS INC.
100 SCHOOL STREET
BERGENFIELD, N.J. 07621-2915

GRSLPFC11-1K-120/240A-XXVDC-1U-LiFe-10M

9812818-SW

CAGE: 29019 SHEET: 1 PAGE 1 REV.

SCALE: 1:3

REV - 9812818-SW-GRSLPFC11-1.K-120-240A-280VDC-CT-2U-LiFe-10M-12818